



THE BETTER ALTERNATIVE TO SOLVENT UNIVERSAL SEAMING ADHESIVE (PATENT PENDING)



TECHNICAL DATA:

Container Sizes:	1 Gallon 5 Gallon 55 Gallon Drums
Film Types:	PVC & PETG
Mileage:	Approximately 160,000 Linear Meters per gallon.
Odor:	Mild Odor
Application:	Works with existing solvent delivery systems: Pump, Gravity or Pressurized Applied with wick or needle
Bond Strength:	Excellent right off machine. Destruct Bond within 24 hours

SAFETY & HANDLING:

Obtain special instructions from MSDS before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Wash face, hands and any exposed skin thoroughly after handling. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/Bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Use explosion-proof electrical (ventilation and lighting) equipment. Keep cool.

STORAGE:

Store locked up, in a well-ventilated place. Keep container tightly

ABOUT UNIVERSAL SEAMING ADHESIVE

Universal Seaming Adhesive (USA) is formulated to be used as a true adhesive for the seaming of shrink sleeves. USA is designed to be used on PVC and PETG shrinkable substrates. Unlike existing seaming solvents that melt the film, and the actual substrate to itself, USA forms a true mechanical bond which allows both edges of the finished tube to be glued to each other.

USA ADVANTAGES:

There are several advantages of using an adhesive over conventional solvents in the market today:

- The biggest advantage of USA is that the adhesive forms a mechanical bond so USA will never migrate through a substrates layers.
- USA offers a 30% to 40% higher yield rate per gallon than conventional seaming solvent when applied at the recommended flow rates. USA only requires a minimum quantity to create acceptable bond strength.
- USA is also more enviromentally friendly than existing seaming solvents. The formula used in USA contains 80% VOC exempt ingredients where existing seaming solvents are almost all formulated with ingredients that are 100% VOC recordable.
- Bond strength and seam clarity is equal to, and in most cases exceeds, finished shrink sleeve industry standards.

UNIVERSAL SEAMING ADHESIVE PRICING

	<u>Size</u>	<u>Cost/Gal</u>
Universal Seaming Adhesive	1 gallon	\$93.00
Universal Seaming Adhesive w/ob	1 gallon	\$98.00
Universal Seaming Adhesive	5 gallons	\$84.00
Universal Seaming Adhesive w/ob	5 gallons	\$87.00
Universal Seaming Adhesive	55 gallons	\$73.00
Universal Seaming Adhesive w/ob	55 gallons	\$74.00

Contact Us Today

AND GET THE ONLY SEAMING ADHESIVE YOU'LL EVER NEED

RYBACK & RYBACK INC.

SALES@RYBACKANDRYBACK.COM

704.774.3274 OR TOLL-FREE 800.564.8099